

DALUB-RDS-015A
ANTIADHERENTE DESMOLDANTE**LUBRICANT FOR RETREADING ENVELOPES**

INTRODUCTION: DALUB-RDS-015, lubricant for envelopes in vulcanization of retreaded tires, does not contain charge and does not contain solvents. It increases the life of the envelopes and produces an excellent lubricating effect. It can also be used as a release agent when the application requires it.

SPECS: DALUB-RDS-015A presents the following characteristics:

- pH	8.5 +/- 1.5	ASTM D1172
- %Solids (2 hours, 105°C)	25.0 +/- 5.0	ASTM D460
- Odor	Characteristic	
- Appearance	White liquid	

FUNCTIONALITY: DALUB-RDS-015 is diluted in water at room temperature up to 50% (50% water, 50% DALUB-RDS-015). It is applied by spray, brush or immersion. The amount applied varies depending on the type of envelop or mold, however, this product is applied in lesser amounts than required with common lubricants.


APPLICATION: DALUB-RDS-015A is applied by spray, brush or immersion. The amount applied varies depending on the type of envelop or mold. If it is stored at low temperature, it should be preheated to room temperature before application

HANDLING: DALUB-RDS-015A is no toxic. It does not present hazard conditions. Normal general security practice is necessary.

STORAGE: DALUB-RDS-015A must be stored between 2 °C to 60 °C. Freezing must be avoided. This product must be used within 12 months of the production date indicated on the packaging.

PACKAGING: DALUB-RDS-015A is available in 5, 15 or 55 gallon containers

REVISÓ:



SC 1600-1