
	SPECIFICATION SHEET	DOCUMENT ID: E-P1-004B VERSION: 03 DATE APPROVED: September 8th, 2020 PAGE 1 of 1
	PRODUCT SPECIFICATION SHEET	

ANTIADHERENTE LUBRICANTE DESMOLDANTE DALUB-RDS 482
TIRE MOUNTING LUBRICANT

- INTRODUCTION:** ANTIADHERENTE LUBRICANTE DESMOLDANTE DALUB-RDS-482, liquid, is a mix of sodium fatty acids stearates. It is used to lubricate the rim tire during the mounting process. It is also used on the tire manufacturing and curing process. It does not contain any mineral charge or silicone. It does not produce foam and is water based. It also has corrosion inhibitor.
- SPECS:** DALUB-RDS-482 presents the following characteristics:
- | | | |
|-------------------------|-------------|-----------|
| -% Solids (105°C, 2 h.) | 10.0 % max. | ASTM D460 |
|-------------------------|-------------|-----------|
- FUNCTIONALITY:** DALUB-RDS-482 can be used as antitack or release agent. It does not present any kind of dust or foam. It has corrosion inhibitor. It can be apply at room temperature.
- APPLICATION:** DALUB-RDS-482 can be applied by brush, spray or sponge.
- HANDLING:** DALUB-RDS-482 is no toxic. It does not present hazard conditions. Normal general security and safety practice is necessary.
- STORAGE:** DALUB-RDS-482 must be stored between 2°C and 60°C. Freezing must be avoided.
- PACKAGING:** DALUB-RDS-482 is available in 5, 15 and 55 gallon containers.

APPROVED BY:




SC 1600-1