

	<b>SPECIFICATION SHEET</b>	<b>DOCUMENT ID:</b> E-P1-012B <b>VERSION:</b> 02 <b>DATE APPROVED:</b> September 8th, 2020 <b>PAGE</b> 1 of 1
	<b>PRODUCT SPECIFICATION SHEET</b>	

**ANTIADHERENTE LUBRICANTE DESMOLDANTE DALUB RDS-482C**  
**TIRE MOUNTING LUBRICANT**  
**CONCENTRATED LIQUID**

**INTRODUCTION:** ANTIADHERENTE LUBRICANTE DESMOLDANTE DALUB RDS-482C, concentrated liquid, is a mix of sodium fatty acids stearates. It is a lubricant used to ease the mounting and dismounting of tires. It is also used on the tire manufacturing and curing process. It does not contain any mineral charge or silicone. It does not produce foam and is water based. It also has corrosion inhibitor.

**SPECS:** DALUB RDS-482C presents the following characteristics:

-%Solids (105°C, 2 h.)	32.0+/- 6.0	ASTM D460
-pH	11.5+/- 2.0	ASTM D1172

**FUNCTIONALITY:** DALUB RDS-482C can be used as antitack or release agent. It does not present any kind of dust or foam. It has corrosion inhibitor. It can be apply at room temperature.

**APPLICATION:** Dilute DALUB RDS-482C with water (room temperature) 1:4. It can be applied by brush, spray or sponge.

**HANDLING:** DALUB RDS-482C IS NOT TOXIC. It does not present hazard conditions. Normal general security and safety practice is necessary.

**STORAGE:** DALUB RDS-482C must be stored between 2°C and 60°C. Freezing must be avoided.

**PACKAGING** DALUB RDS-482C is available in 5, 15 and 55 gallon containers.



SC 1600-1

APPROVED BY: 