

**DL-PIC-427 CH**

## WATER-BASED RUBBER REPAIR PAINT

**INTRODUCTION:** DL-PIC-427 CH is a water-based rubber repair paint (no VOC). It covers all blemish, scuff marks, crayon marks and chalk on cured, repaired or retread tires or different rubber products. It is for post-cure use and the application method can be spray, brush or sponge. This product gives an excellent appearance to the cured tire and presents very quick drying time at room temperature.

**SPECS:** DL-PIC-427 CH presents the following characteristics:

pH	7.50+/-2.0	ASTM D460
%solids	26.0+/-5.0	ASTM D1172
Appearance	Black liquid	

**FUNCTIONALITY:** DL-PIC-427 CH is applied to the outside of the vulcanized, repaired or retreaded tire. The amount to use depends on the process and the size of the tire.


**APPLICATION:** DL-PIC-427 CH can be applied by spray, brush or sponge at room temperature not higher than 55 ° C. In case of light precipitation during a long period of storage, it is necessary to stir it for a few seconds. If it is stored in cold temperature allow product to warm to room temperature before use.

**HANDLING:** DL-PIC-427 CH is no toxic. It does not present hazard conditions. Normal general security practice is necessary.

**STORAGE:** DL-PIC-427 CH must be stored between 2°C to 60°C. Freezing must be avoided.

**PACKAGING:** DL-PIC-427 CH is available in 5, 15 gallon or 55 gallon containers.

APPROVED BY:



SC 1600-1