

	PRODUCT SPECIFICATION SHEET	DOCUMENT ID: E-P1-022B VERSION: 04 DATE UPDATED: January 30, 2023 PAGE 1 of 1
	DALUB-RDS-015	

DALUB-RDS-015 ANTIADHERENTE DESMOLDANTE

LUBRICANT FOR RETREADING ENVELOPES

INTRODUCTION:	DALUB-RDS-015, lubricant for envelopes in the vulcanization of retreaded tires, contains no solvents and no fillers. It increases the service life of the envelopes and produces an excellent lubricating effect. It can also be used as a release agent when the application requires it.		
SPECIFICATIONS:	DALUB-RDS-015 presents the following characteristics:		
	- pH	8.5 +/- 1.5	ASTM E70-07
	- % Solids (105°C, 2 h)	35.0 +/- 5.0	ASTM D460
	- Color	White	
	- Odor	Characteristic	
	- State	Liquid	
FUNCTIONALITY:	DALUB-RDS-015 is diluted in water at room temperature up to 25% (75% water, 25% DALUB-RDS-015). It is applied by spray, brush or immersion. The amount applied varies depending on the type of envelope or mold; however, this product is applied in smaller amounts than those required with common lubricants.		
APPLICATION:	DALUB-RDS-015 is applied by spray, brush, sponge or immersion. The weight of lubricant applied depends on the size of the envelope or mold. If it is stored at low temperature, it should be preheated to room temperature before application.		
HANDLING:	DALUB-RDS-015 is non-toxic and does not present hazardous conditions. Only the normal precautions of standard industrial practice are required for handling and storage.		
STORAGE:	DALUB-RDS-015 must be stored between 0°C and 60°C. Freezing must be avoided. This product must be used within 12 months of the production date indicated on the packaging.		
PACKAGING:	DALUB-RDS-015 is available in 5, 15 or 55 gallon containers.		

REVIEWED BY: I.V.



SC 1600-1