

	PRODUCT SPECIFICATION SHEET	DOCUMENT ID: E-P1-003B VERSION: 09 DATE UPDATED: March 20, 2026 PAGE 1 of 1
	DALUB-RDS-425	

ANTIADHERENTE DESMOLDANTE DALUB-RDS-425
 LIQUID ANTI-TACK RELEASE AGENT FOR EXTRUSION

INTRODUCTION:	DALUB-RDS-425 is an excellent alternative to prevent jamming and rubber sticking on extruder heads, dies and inserts in extrusion processes. It is a water-based product and contains no solvents or silicones. It also provides an excellent non-stick effect on molds and compound sheets. It contains no minerals or other fillers.		
SPECIFICATIONS:	DALUB-RDS-425 presents the following characteristics:		
	- % Solids	12.5% +/- 2.5%	ASTM D460
	- pH	10.5 +/- 1.5	ASTM E70-07
FUNCTIONALITY:	DALUB-RDS-425 has a great non-stick effect between rubber sheets and does not present dusting or pollution problems. This solution can be used as a release agent with optimal results. It is not necessary to heat it for use.		
APPLICATION:	It can be applied by immersion, spray or brush. If the product appears cloudy, it must be stirred to dissolve the suspended sodium stearate particles.		
HANDLING:	DALUB-RDS-425 is non-flammable. Only the normal precautions of standard industrial practice are required for handling and storage.		
STORAGE:	DALUB-RDS-425 must be stored in a dry place at 2°C to 60°C. Freezing must be avoided.		
PACKAGING:	DALUB-RDS-425 is available in 1, 5 or 55 gallon containers, or as required by the customer.		

APPROVED BY: I.V.



SC 1600-1