

	PRODUCT SPECIFICATION SHEET	DOCUMENT ID: E-P1-004B VERSION: 04 DATE UPDATED: January 23, 2023 PAGE 1 of 1
	DALUB-RDS-482	

ANTIADHERENTE LUBRICANTE DESMOLDANTE DALUB RDS-482
LIQUID LUBRICANT AND RELEASE AGENT FOR TIRE MOUNTING

INTRODUCTION:	Liquid DALUB-RDS-482 is a mixture of sodium stearates of unsaturated fatty acids. It is used for tire mounting and for bead lubrication in balancing machines and F.V.M. It contains no fillers or any type of mineral. It does not produce foam. It contains no solvents.
SPECIFICATIONS:	DALUB-RDS-482 presents the following characteristics: - % Solids (105°C, 2 h) 10.0% Max. ASTM D460
FUNCTIONALITY:	It has a great lubricating effect between the rim, the bead, the ring or any other metal part. It does not present foam, dusting or pollution problems. This solution can be used as a release agent with optimal results. It is not necessary to heat it for use.
APPLICATION:	It can be applied by immersion, spray or brush.
HANDLING:	DALUB-RDS-482 is non-flammable. Only the normal precautions of standard industrial practice are required for handling and storage.
STORAGE:	DALUB-RDS-482 must be stored in a dry place at 2°C to 60°C. Freezing must be avoided.
PACKAGING:	DALUB-RDS-482 is available in 5, 15 or 55 gallon containers.

APPROVED BY: I.V.

