

	PRODUCT SPECIFICATION SHEET	DOCUMENT ID: E-P1-006B VERSION: 04 DATE UPDATED: January 23, 2023 PAGE 1 of 1
	DL-PIC-427CH	

WATER-BASED RUBBER PAINT FOR TIRE REPAIR AND FINISHING
DL-PIC-427CH

INTRODUCTION:	DL-PIC-427 CH is a water-based rubber paint that contains no aromatic solvents (no VOC). It covers all surface marks on vulcanized, repaired or retreaded tires. This paint dries very quickly and does not peel or stain after application. It can be used on other vulcanized rubber products.		
SPECIFICATIONS:	DL-PIC-427 CH presents the following characteristics:		
	pH	7.50 +/- 2.0	ASTM E70-07
	% Solids (105°C, 2 h)	26.0 +/- 5.0	ASTM D460
	Appearance	Black liquid	
FUNCTIONALITY:	This paint is formulated to cover scratches, scuffs and peeled areas on the tire.		
APPLICATION:	DL-PIC-427 CH is applied to the outside of the tire by spray, brush or sponge. The amount to use depends on the surface to be covered. Separation may be observed after a long storage period, in which case the product must be stirred for a few seconds. Avoid freezing the product.		
HANDLING:	DL-PIC-427 CH is non-toxic and does not present hazardous conditions. Normal safety and handling practices are required.		
STORAGE:	DL-PIC-427 CH must be stored between 2°C and 60°C. Freezing must be avoided.		
PACKAGING:	DL-PIC-427 CH is available in 5, 15 and 55 gallon containers.		

APPROVED BY: I.V.



SC 1600-1